





SS-ASR *Miniature Mono Surveillance Recorder Modules*

Range Summary

Model	Dims. (mm)	Weight (gm)	Memory capacity (MBytes)	Standard Accessories	Optional Accessories	Power supply
M1 	39 x 14 x 4	2	64 – 512	<ul style="list-style-type: none"> Controller Software 	<ul style="list-style-type: none"> Transition adapter PC connection cable 	3V DC
M2 	41 x 21 x 6	4	1024 – 2048	<ul style="list-style-type: none"> Controller Software 	<ul style="list-style-type: none"> Transition adapter PC connection cable 	3V DC
M3 	54 x 21 x 6	8	4096	<ul style="list-style-type: none"> Controller Software 	<ul style="list-style-type: none"> Transition adapter PC connection cable 	3V DC
MS5 	23 x 18 x 5	1	64 – 512	<ul style="list-style-type: none"> Controller Software 	<ul style="list-style-type: none"> Transition adapter with telephone recorder adapter PC connection cable 	3V DC

Recording Quality and Duration

Model	Flash Memory (MBytes)	Quality Setting:	ExtraLongPlay	LongPlay	Medium	Normal	High
		Bit-rate:	16 kbits/sec	24 kbits/sec	32 kbits/sec	64 kbits/sec	96 kbits/sec
		Compression:	modified 2-bit IMA ADPCM	modified 3-bit IMA ADPCM	modified 4-bit IMA ADPCM	linear 8-bit μ -Law	linear 12-bit uncompressed
M1-560	64 MBytes		560 mins	373 mins	280 mins	140 mins	93 mins
M1-1120	128 MBytes		1120 mins	747 mins	560 mins	280 mins	187 mins
M1-2240	256 MBytes		2240 mins	1493 mins	1120 mins	560 mins	373 mins
M1-4480	512 MBytes		4480 mins	2987 mins	2240 mins	1120 mins	747 mins
M2-8960	1024 MBytes		8960 mins	5973 mins	4480 mins	2240 mins	1493 mins
M2-17920	2048 MBytes		17920 mins	11947 mins	8960 mins	4480 mins	2987 mins
M3-35840	4096 MBytes		35840 mins	23983 mins	17920 mins	8960 mins	5973 mins